

April 1, 2004

Mr. Bill Storm Environmental Quality Board 658 Cedar Street St. Paul, MN 55155



Re: Comments on the Environmental Impact Statement for Faribault Energy Park

Dear Mr. Storm:

Thank you for the opportunity to comment on the Environmental Impact Statement (EIS) for Faribault Energy Park (FEP) to be built in Rice County. This comment letter addresses matters of concern to Minnesota Pollution Control Agency (MPCA) staff reviewing the EIS. MPCA staff is submitting the following comments for your considerations and response before a final determination on an adequacy decision is made for this project.

### Air Emissions Risk Analysis (AERA)

Section H.1. of the scoping document requires the EIS to include information from FEP's AERA. FEP submitted AERA documents to the Environmental Quality Board (EQB) and the MPCA on February 20, 2004. MPCA staff did not have time to complete their review of the AERA prior to the EIS's public release date of March 1, 2004. MPCA staff worked with FEP during the public comment period in order to correct and refine the AERA information. Because the AERA information was updated after the EIS was put on public notice, the AERA information contained in the draft EIS was obsolete (Tables 13-17, and 19). The enclosures to this letter include all the updated AERA tables and information that should be made available for public review. With the inclusion of this additional information, the MPCA would find the EIS adequate for an air emissions risk analysis.

The purpose of the AERA is to aid the MPCA in examining possible health risks from a list of toxic chemicals and to help the public understand those risks. In simple terms, the AERA is a screening tool that allows the MPCA to examine health risks from chemicals that are emitted from a facility. The AERA uses conservative assumptions to determine if a more refined risk assessment is necessary. The term "risk" generally refers to estimated cancer risks and the potential for noncancer health effects. Noncancer health effects are described using a hazard quotient (for a single chemical) or a hazard index (the sum of hazard quotients for all noncancer chemical exposures). In the AERA process, "quantitative analysis" specifically refers to the estimation of cancer risks and hazard indices using the Risk Assessment Screening Spreadsheet (included in the enclosures). The AERA process additionally includes a "qualitative analysis," which identifies issues for which public health impacts cannot easily be easily quantified.

The MPCA managers met on March 29, 2004, to hear and discuss staff's findings on the AERA. After consideration of the information, the managers concluded that the AERA was complete, and that the impacts associated with the air emissions that are reasonably expected to occur from this project have been adequately characterized.

### Other Comments on the Draft EIS

The following comments are meant to clarify wrong or missing information in certain sections of the EIS.

### 4.5 Wastewater

This section states that the project will need to obtain a National Pollution Discharge Elimination System/State Disposal System (NPDES/SDS) permit from the MPCA. However, this permit is missing from the permit requirements in Table 24. Table 24 should read, "NPDES/SDS permit for non-contact cooling water."

The project does not identify any disposal of industrial wastewater. MPCA staff questions whether the only wastewater will be from noncontact cooling water and sanitary sources. Will they have water generated from a maintenance washing area or other nondomestic sources?

### 6.11 Hazardous Wastes

The federal designation of Conditionally Exempt Small Quantity Generator is not used in Minnesota, as Minnesota rules are more stringent. The correct hazardous waste generator designation for this facility is Very Small Quantity Generator (VSQG). Through this designation, the facility would be required to obtain a U.S. Environmental Protection Agency (EPA) ID number. This number is acquired through the MPCA. In addition, Table 24 lists FEP as needing to register as a Small Quantity Generator. This should read VSQG.

### 6.2.1 Water Resources - Surface Water

According to the 1996 National Water Quality Inventory, stormwater runoff is a leading source of water pollution. The EPA estimates that 20 to 150 tons of soil per acre is lost to stormwater runoff from construction sites. Many studies indicate that controlling erosion can significantly reduce the amount of sedimentation and other pollutants transported by runoff from construction sites.

To that end, the MPCA's Stormwater Program for construction activity is designed to reduce the amount of sediment and pollution entering surface and ground water both during and after construction projects. Stormwater discharges associated with construction activities are regulated through the use of NPDES permits. Through this permit, the owner is required to develop a stormwater pollution prevention plan that incorporates specific best management practices applicable to their site.

Mr. Bill Storm April 1, 2004 Page 3

The sections that address stormwater do not seem to recognize Minnesota's new General Stormwater Permit for Construction Activity. The new permit, which went through extensive public comment, became effective on August 1, 2003

(http://www.pca.state.mn.us/water/stormwater/stormwater-c.html). The new program is called "Phase II Construction Stormwater Permit" (Phase II). (The Phase I Construction Stormwater permit program expired on September 3, 2003.) Phase II requires a Stormwater Pollution Prevention Plan (SWPPP), which is more comprehensive than the Temporary Erosion and Sediment Control Plans mentioned in the EIS. The SWPPP requires narratives, standard plates, identifies who will perform inspections and maintenance, and other requirements. In addition, Phase II allows for more options for permanent stormwater treatment. The proposed stormwater retention pond is likely adequate; however, FEP may want to review the Phase II rules for more options as they prepare their final design.

And last, section 4.9 briefly describes best management practices (BMPs) to be employed during site development. While this is a good list, FEP should make sure they are implementing BMPs in accordance with Phase II.

### Comments on Sections Related to Air Quality

### **Executive Summary**

In the fourth paragraph from the end, the EIS states "...FEP will comply with the lowest achievable emission rate established under the Federal Clean Air Act." This is incorrect. FEP will meet Best Available Control Technology (BACT), not lowest achievable emission rate (LAER).

### 4.7 Air Emission Control Equipment

In the fifth paragraph under this section, it states, "Once the Minnesota Pollution Control Agency (MPCA) reviews the Prevention of Significant Deterioration (PSD) Air Quality Permit application, the MPCA may require that the facility utilize an oxidation catalyst as an addition to the proposed air emission control equipment to further reduce emissions of CO and VOCs." MPCA staff has now reviewed the application, and will not require an oxidation catalyst at this time.

### 6.4 Air Quality

Section D.3. of the scoping document states that the EIS will address carbon dioxide emissions. A discussion of this pollutant appears to be missing.

### Table 10

The asterisk at the bottom of the table should read:

\*Worst case NOx and SO2 emissions occur at 100% load during normal operation <u>for 2500 hours per year</u>, <u>iunlike PM?/PM10</u>, CO, and VOC worst case emissions, which occur during startup and shutdown.

Mr. Bill Storm April 1, 2004 Page 4

Also in table 10, the value for NOx across from the "Combustion Turbine Subtotal" should read "48.83."

### Table 11

For acrolein, the potential emissions in pounds per year should read "105" instead of "10.5."

If you have questions regarding these comments, please call me at (651) 297-1766.

Sincerely,

Susan Heffron

**EQB** Technical Representative

SH:mbo

**Enclosures** 

cc: David Thornton, MPCA

1a`	AQ Facility ID No.: 13100071
	AQ File No.: 4131
2)	Facility Name: Faribault Energy Park
3)	Date of Submittal:
4)	Date Summary given to Managers: DRAFT on 3/25/04, 3/26/04, Presented at meeting 3/29/04
 5)	Date of Decision: 3/31/04

### 6) General Assessment Considerations

- PTE emission estimates of fuel oil combustion. For simple cycle this assumes a maximum of 500 hours operation and for combined cycle it assumes 8760 hours per year.
- Refined modeling "at and beyond" the fence line for "high first high" concentration
- Resident and subsistence farmer scenarios are each plausible. Resident at farm house located near area of maximum modeled 1 hour impacts and annual impacts from simple cycle operation.
- Per AERA guidance, risks not quantified from: natural gas combustion, diesel emissions, majority of the VOC emissions, fish consumption pathway (fishable water bodies are located near the proposed facility), criteria pollutants (other than lead and acute NOx)

### 7) Quantitative Risk Estimates and Associated Qualitative Factors:

### Simple Cycle

- No risks exceeded the criteria, no modeled concentrations exceeded the ceiling values for developmental effects.
- The acute HQ for NOx was 0.3, other chemical risks below 0.1 HQ and 10-6 cancer risk criteria
- Risks estimated based on 7% of VOCs and 100% of identified HAPS

	Air Toxics Screen													
Total in	halation Scre and Can		d Indices			ay Screenin Cancer Risk		Total Multipathway Screening Hazard Indice and Cancer Risks						
Acute	Subchroni c Noncancer	Chronic Noncance r	Сапсег	Farmer Noncance r	Farmer Cancer	Resident Noncance r	Resident Cancer	Farmer Noncance r	Farmer Cancer	Resident Noncance r	Resident Cancer			
3(35- <b>0</b> )	33(6€36)73	STE_1021	(5):/(224 <b>6)</b> e)	1:11=07	24:12:08		.1.7/EL(p)	i[J∄E≟iYi)	5445±00	), <b>a</b> =.0.5	(6.4⊑(			
(10E±00	1.0E+004	1-0E+00	10E-05	1.0E+00	1.0E-05	1'0≡¥00	. <u>-1.0</u> E205	1.0=400°	(10)≟05	10E+00	10E40			
ΘK	** *@K *-2*	ok =	#EOKs	ΘK	, oks a		racok ra	οκ	°OK	łok	eK eK			

### **Combined Cycle**

- Additional lifetime cancer risk estimate for subsistence farmer is 5 x 10-5
- No modeled concentrations exceeded the ceiling values for developmental effects.
- Majority of additional cancer risk is based on estimated POM emissions assessed using uncertain, likely conservative, benzo(a)pyrene surrogate
- Majority of additional cancer risk is derived from estimated ingestion exposures
- Risks based on 2% of VOCs and 100% of identified HAPs

	Air Toxics Screen													
Total in	halation Scre and Can	ening Hazar cer Risks	d Indices	Total Indirect Pathway Screening Hazard Indices and Cancer Risks				Total Multipathway Screening Hazard Indices and Cancer Risks						
Acute	Subchroni c Noncancer	Chronic Noncance r	Cancer	Farmer Noncance r	Farmer Cancer	Resident Noncance r	Resident Cancer	Farmer Noncance r	Farmer Cancer	Resident Noncance r	Resident Cancer			
(15,0)	1:35:00	201 <b>5</b> .00	1.15400	1 ( <b>3</b> E-19:)	43F=05		it (15497)	%.(E-05)	43 76 8 10 5	2,451.492	នគ.ពភ			
4.0EY00	4 % OE+00	1.0E+00	1.0E:05	1.05000	11.0E.05	'asl 0⊟+00'.	1,0E-05	1.0E400	(F0E+05	1.05100				
OK	ØK.	:OK	ОK	οĸ	REFINE		őк	ок (	REFINE	i i i	OK.			

### 8) Dispersion Modeling Comments and Recommendations: Approve dispersion modeling portion of AERA. Results are likely more accurate and less conservative that dispersion factors from RASS look-up tables or DISPERSE program.

### 9) Emission Calculations: Comments and Recommendations:

RASS emissions data was reviewed and corrections were made by the Permittee in response to the permit writer's review of the data. Although available information was utilized, emission factors are unavailable for some of the numerous chemicals of combustion.

PERMIT STAFF INFORMED FEP OF THE EXCESSIVE FARMER CANCER RISK, AND THAT THE RISK MANAGERS WILL BE CONSIDERING THIS ISSUE WHEN THEY MAKE A DETERMINATION ABOUT THE OVERALL RISK FROM THE FEP PROJECT. THIS INFORMATION WAS CONVEYED THROUGH VERBAL TELEPHONE AND EMAIL COMMUNICATIONS. THE INFORMATION WAS PROVIDED IN RESPONSE TO FEP'S INQUIRY ABOUT THE STATUS AND TIMELINE OF THE PERMIT PUBLIC NOTICING.

Additional Qualitative Considerations Include:



**Nearby Receptors:** No sensitive receptors were identified within a kilometer of the proposed facility. There appears to be a farm house northeast of the proposed facility. The site vicinity is sparsely populated, with more densely populated areas of Fairbault located a mile to the south. The population surrounding the proposed facility may increase if Fairbault expands to the north. The vicinity is currently agricultural. See the census maps of the proposed facility vicinity.

**Nearby Facilities (within 1 mile)**: Williams Pipeline Co., Primera Foods Inc., and the airport are located roughly within a mile of the site. Traffic from the nearby I-35 and other local roads is an additional source of air pollution near the site.

Accidental Releases: NA

**Diesel Generators**: During testing and emergency use, diesel engine exhaust, which is composed of NOx, SO2, various air toxics, PAHs, fine particles and other chemicals. Hazards associated with exposures to diesel exhaust include respiratory irritation. Longer term exposures may result in cancer and chronic bronchitis. The emergency generator and fire pump engines would be tested once per week.

**Direct PM<sub>2.5</sub> Emissions:** PM2.5 emissions were estimated using emission factors developed by EPA for its National Emission Inventory

(ftp://ftp.epa.gov/EmisInventory/prelim2002nei/point/documentation/egu2002nei\_final.pdf). The estimates take annual limits on fuel oil use into account but assume emissions are uncontrolled. Faribault Energy Park will employ good combustion practices but will not add any control equipment for PM10 or PM2.5.

The PM2.5 emission estimates for the two operating scenarios are 1.76 tpy and 6.82 lb/hr for the simple cycle turbine, 34.2 tpy and 7.80 lb/hr for the combined cycle turbine, and 0.315 tpy (0.0720 lb/hr) for the boiler. The boiler will only run during combined cycle operation. Annual PM2.5 emissions from the combined cycle turbine are relatively higher than those from the simple cycle turbine due to higher limits on fuel oil burning. As shown, hourly emissions for the two scenarios are similar.

**Air Monitoring Results**: Ambient air pollutant monitoring data for air toxics and criteria pollutants, collected from the statewide monitoring program, are summarized in the attached graphics. A summary of the recently monitored air toxic concentrations in the Twin Cities Metropolitan Area is available at

http://www.pca.state.mn.us/hot/legislature/reports/2003/lr-airtoxmonitoring-1sy03.pdf. In general, the statewide air toxics monitoring data has found that benzene and formaldehyde are routinely measured at levels near or above their respective inhalation health benchmarks (based on 10-5 additional cancer risk levels). A significant portion of the statewide inventory of these pollutants is from mobile sources. The concentrations of these pollutants have been found to be somewhat higher in urban areas than in the rural areas. This generalization has been found in MN and nationally. Cities size of Fairbault have generally been found to have air toxic concentrations on the order of those found in the Twin Cities suburbs, such as Apple Valley. With respect to PM2.5, average annual concentrations in the southern

half of Minnesota range between 9 ug/m3 and 12 ug/m3 (compared to an annual standard of 15 ug/m3). No Minnesota monitoring data is available for PAHs or POM.

MN Emission Inventory Info: For reference, the 1999 emission inventory (estimated actual emissions) for POM, PAH and 7-PAH was sorted and the top facility emissions are listed on the attachments. Note that the AERA emission estimates are PTE, so these will clearly be higher than those estimated for the emission inventory. However, for reference, the fuel oil estimates for combined cycle PAH are 0.039 tpy and for POM 0.0027 tpy. For POM, this would implies that the combined cycle would emit less than the 84th facility in the statewide ranking for this specific pollutant, and for PAH the combined cycle estimated PAH PTE is higher than all but one facility in the state (reported actuals).

Respiratory Sensitizers: Beryllium and nickel are emitted from fuel oil combustion. As for all respiratory sensitizers, although their concentrations are well below their respective health benchmarks, due to the variable nature of the allergic response in sensitized individuals, it is not possible to predict at what the concentration a previously sensitized may experience adverse effects.

**Developmental Toxicants**: These include arsenic, benzene and mercury from the simple cycle; and arsenic, benzene, mercury and ethyl benzene from the combined cycle. None were above their respective ceiling values. In addition, although carbon tetrachloride and chloroform may possibly be emitted, quantitative emission estimates were unavailable.

Community Concerns: None have been identified

### **State and Federal Requirements:**

What state and federal control requirements apply? BACT is required for combined cycle operation. Source is an affected source under part 63 subp. YYYY for combustion turbines, but the source is not a major HAP source so subp. YYYY does not apply

Demonstrated technical	feasibility: Catalyt	c Oxidizer is technically	y feasible for
CO, which also would c	control organic HAP	5.	

<u>Demonstrated economic feasibility:</u> Catalytic oxidizer is not economically feasible according to the BACT analysis. Good combustion practice is BACT, for CO, which will also minimize organic HAP. GCP includes limits for operating in startup/.shutdown mode when CO and organic HAP emissions are highest.

If hazard indices exceed 1 and cancer risks exceed 10<sup>-5</sup>, does the project have a reasonable level of emissions control? Yes, the combined cycle combustion turbine will have a reasonable level of control (good combustion practices)

Conservativeness of the Quantitative Analysis (i.e., underestimates potential health risks?): Especially with respect to the combined cycle operations, which were assumed to burn fuel oil 8760

### **AERA-IF-0F** RISK MANAGEMENT AERA SUMMARY

February 2004

hours/year, this is a conservative assumption. Using benzo(a)pyrene as a surrogate for POM and PAH is also considered conservative (in addition to being quite uncertain). Limitations in the emission factor databases result in significant additional uncertainties. The refined dispersion analysis was not very conservative, especially compared to the screening level modeling available in the RASS lookup table. Most of the estimated risks are derived from the multimedia ingestion exposure route. Due to the multimedia modeling complexity, and the exclusion of the fish consumption scenario, this is relatively more uncertain than the inhalation route risks. The conservativeness of the multimedia modeling for a subsistence farmer is unknown. Because only a small fraction of the VOCs were assessed, this is not conservative. Following general EPA guidance, the AERA process estimates total hazard indices and cancer risks for air toxics (summary table section 7), however this estimate does not account for risks from criteria pollutants. In this respect, the risk estimates are not conservative.

### Considerations for analysis:

- 1. Issues that can be clarified through a refined analysis: Use of future actual emissions rather than PTE emissions (accompanied by an appropriate permit limit). The following would help refine the analysis but would be resource-intensive:
  - Review of the multimedia modeling approach and assumptions, including the use of site-specific factors (which would include assessing the fish consumption from the lakes),
  - Improved emission estimates to include more of the mass emitted,
  - Speciation of the POM and PAH mass emissions &/or development of a toxicity value for the fuel oil combustion mixture

	· · · · · · · · · · · · · · · · · · ·		 	
Staff team recommendation	ons:		•	
Additional refinements lists currently included in the sc	ope of the analysis,	, would resul	•	,
that it would be meaningful	to further refine th	nis analysis.	 	<del></del> .
that it would be meaningful	to further refine th	nis analysis.	 	
that it would be meaningful	to further refine th	is analysis.		
that it would be meaningful	to further refine th	nis analysis.		
that it would be meaningful	to further refine the	nis analysis.		

### **Decision options:**

- 1. Refined assessment needed
- 2. Facility risk analysis is complete. Env. Review and/or permitting proceeds.
- 3. Request mitigative measures
- 4. Recommend EIS

Decision:	Facility	risk analysis is	complete.	<b>Environmental Review</b>	and/or permitting proceeds.
			•		

### **Management Rationale:**

The MPCA Risk Managers met on March 29, 2004 to discuss this AERA. Staff presented the information contained in this document and discussed their conclusions and concerns.

After consideration of all of this information the Risk Managers conclude that the facility air risk analysis is complete and that the impacts associated with air emissions that are reasonably expected to occur from this project do not have the potential for significant environmental or health effects.

In reaching this decision and conclusion, the Risk Managers note the following:

1) Emissions were estimated based on full-time operation (8760 hours per year) with fuel oil. This facility is intended to operate as an intermediate load plant with natural gas as its primary fuel. Thus the emissions assumed in the analysis represent a significant over estimate of the emissions that would be reasonably expected to occur. 2) Mercury emissions estimated from AP-42 may be unreliable. Other data suggests emissions would be insignificant (<1 lb/yr.) 3) The maximum expected risk is for a farmer ingesting food grown at the sight of maximum impact. The point of maximum exposure for the farmer is just outside the fence line of the facility. This represents an exposure scenario that is not likely to occur. In addition, the farmer risk is based on the assumption that all POM and PAH is benzo(a)pyrene, This is a conservative assumption. Any attempt to speciate further is only likely to reduce the risk. Therefore the estimated farmer risk is considered to be an overestimate while taking into account the uncertainties summarized above.

Section Manager Signatures and dates

3/31/04 MIQ I I llt 3/3/04 Marsham 3/3/104

### Summary of Quantitative Results of the AERA

### RASS version number = 20040302

Facility Name: User Title: Type of emissions

Faribault Ener	gy Park									
FEP Combine	d Cycle Calcul	ations Februar	y 2004 Version							
PTE		\ \								
Criteria Pollutant Screen										
Chemical				dragion of						
SO2	0:027	1 1 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2	100000		0,003					
PM10			0.345		0.011					
PM2.5			2, 5,95							
NOx					0;005					
co	0.010			inglikasinatoni varo mak. v						
Pb				0.000						

					Air Toxic	s Screen			er Egerbri. Heregasi ili		
Total ini	nalation Scree Canc	ning Hazard er Risks	Indices and	Total Indire		Screening Ha	zard Indices	19.1 165 February 1984 (1984)	the state of the state of	y Screening Cancer Risk	1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1
Acute	Subchronic Noncancer	Chronic Noncancer	Cancer	Farmer Noncancer	Farmer Cancer	Resident Noncancer	Resident Cancer	Farmer Noncancer	Farmer Cancer	Resident Noncancer	Resident Cancer
dida(iii)	00€00	2/3=202	1V4E-06	t@202	2001≩06		1.93-07	72.T≩ i)/2	475.00	2412-09	04040
1.0E+00	1.0E+00	1.0E+00	1.0E-05	1.0E+00	1.0E-05	1.0E+00	1.0E-05	1.0E+00	1.0E-05	1.0E+00	1.0E-0
ок	ок	ок	OK	ок	REFINE		ok .	ок	REFINE	ок	ок

<<Acceptable Level <<<OK or Not?

Fraction of VOC	s assessed	64 <b>10</b> 02 10 02	ì
Fraction of HAF	sassessed	<b>(4)</b>	j

Total Criteria Pollutant Emissions (tpy)	1537.146
Total HAP Emissions (tpy)	13.884
Total VOC Emissions (tpy)	350.052

Ceiling Values Exceeded?									
Benzene	no								
Carbon disulfide	no								
Cellosolve Acetate	no								
Chloroform	no								
2-ethoxyethanol	no								
Ethylbenzene	no								
Ethyl chloride	no								
2-methoxyethanol	no								
Trichloroethylene	по								
Arsenic	по								
Carbon tetrachloride	no								
Mercury	no								
Propylene oxide	no								

### AERA Screening Level Estimated Risks for Inhalation Exposures, Ingestion Exposures and for the Combination of Inhalation and Ingestion

Facility Name: Faribault Energy Park
User Title: FEP Combined Cycle Calculations February 2004 Version

	User Title:	FEP Combined Cycle Calculations February 2004 Version							<u></u>	Compagness a 200 formation of the contract of					
cas # or MPCA #	Chemical Name					Chronic Screening Non-inhalation Pathway Hazard Quotients and Cancer Risks for Individual Substances				Chronic Screening Total Hazard Quotients and Cancer Risks (Inhalation + Non-Inhalation) for Individual Substances					
		Acute ISHQ	Subchronic Noncancer ISHQ	Chronic Noncancer ISHQ	ISIR(ca)	Farmer Noncancer	Farmer Cancer	Resident Noncancer	Resident Cancer	Farmer Noncancer	Farmer Cancer	Resident Noncancer	Resident Cancer		
7664-41-7	Ammonia	3.2E-03	1.0E-03	5.1E-04				=		5.1E-04		5.1E-04			
7440-38-2	Arsenic	3.3E-02		2.3E-03	2.9E-07					2.3E-03	2.9E-07	2.3E-03	2.9E-07		
56-55-3	Benz[a]anthracene	:			2.4E-11		2.4E-09		6.3E-11		2.4E-09	······································	8.6E-11		
71-43-2	Benzene	2:8E-05		6.8E-06	1.6E-09					6.8E-06	1.6E-09	6.8E-06	1.6E-09		
207-08-9	Benzo(k)fluoranthene				8.6E-12		5.2E-09		9.6E-12		5.2E-09		1.8E-11		
50-32-8	Benzo[a]pyrene												<u> </u>		
205-99-2	Benzo[b]fluoranthene				8.6E-12		2.6E-09	, .	1.3E-11		2.6E-09		2.1E-11		
7440-41-7	Beryllium			1.2E-03	5.5E-08		1.6E-07		4.3E-08	1.2E-03	2.1E-07	1.2E-03	9.9E-08		
106-99-0	Butadiene, 1,3-			2.8E-05	1.6E-08					2.8E-05	1.6E-08	2.8E-05	1.6E-08		
7440-43-9	Cadmium			1.9E-03	7.0E-08	.•	7.0E-07	·	1.3E-07	1.9E-03	7.7E-07	1.9E-03	2.0E-07		
18540-29-9	Chromium (Hexavalent) (particulate)		1.4E-04	6.1E-04	7.3E-07					6.1E-04	7.3E-07	6.1E-04	7.3E-07		
218-01-9	Chrysene (Benzo(a)phenanthrene)				1.4E-12		2.8E-10		4.4E-12	-	2.8E-10		5.8E-12		
7440-50-8	Copper	1.1E-05													
53-70-3	Dibenz[a,h]anthracene				1.1E-10		4.2E-07		7.3E-11		4.2E-07		1.8E-10		
100-41-4	Ethyl benzene	8.8E-09		3.4E-09						3.4E-09		3:4E-09			
50-00-0	Formaldehyde	2.0E-03		9.1E-04	3.5E-08					9.1E-04	. 3.5E-08	9.1E-04	3.5E-08		
193-39-5	Indeno(1,2,3-cd)pyrene				1.2E-11		7.5E-07		4.5E-11		7.5E-07		5.7E-11		
7439-92-1	Lead				1.4E-09	_	2.6E-09			<del></del>	4.0E-09		1.4E-09		
7439-96-5	Manganese			1.4E-02						1.4E-02		1.4E-02			
7439-97-6	Mercury	6.5E-04	3.3E-04	1.6E-04		1.6E-04				3.2E-04		1.6E-04			
91-20-3	Naphthalene	9.5E-05		2.0E-05				<del></del>	-	2.0E-05		2.0E-05			
7440-02-0	Nickel	2.6E-04		7.6E-04	9.9E-09					7.6E-04	9.9E-09	7.6E-04	9.9E-09		
	Nitrogen oxide (NO2) Polycyclic Aromatic Hydrocarbons	5.4E-02								:					
130498-29-2					1.9E-08		5.8E-06				5.8E-06		1.9E-08		
00-01-7	Polycyclic Organic Matter (POM)				1.3E-07		3.8E-05				3.8E-05		1.3E-07		
7784-49-2	Selenium			9.9E-06						9.9E-06	-	9,9E-06			
108-88-3	Toluene	4.0E-06		3.2E-06				· :		3.2E-06		3.2E-06			
1330-20-7	Xylenes	2.2E-06		6.7E-06						6.7E-06		6.7E-06	<del></del> .		
7440-66-6	Zinc				,										
00-03-3	Zinc Compounds														

### Estimated Air Concentrations Used for the AERA

Facility Name: User Title:

Faribault Energy Park
FEP Combined Cycle Calculations F

Air Concents	rations in ug/m³	User Title		tal - all st	ined Cycle Ca acks	
-	ations in ug/in		T	rtai - axi sti	l l	<u> </u>
CAS # or MPCA #	Chemical Name	C (1-hr)	C (3-hr)	C (24-hr)	C (monthly)	C (annual)
SO2	SO2	3.5E+01	2.9E+01	8.1E+00	3.4E-01	1.6E-01
PM10	PM10	2.8E+02	2.4E+02	5.2E+01	1.3E+00	5.5E-01
PM2.5	PM2.5	0.0E+00	0.0E+00	0.0E+00	0.0E+00	0.0E+00
NOx	NOx	2.5E+01	2.0E+01	6.4E+00	1.0E+00	4.8E-01
CO	со	3.4E+02	2.9E+02	6.3E+01	1.0E+00	4.5E-01
Pb	Pb	8.7E-03	7.3E-03	1.9E-03	2.6E-04	1.2E-04
7664-41-7	Ammonia	1.0E+01	8.9E+00	1.9E+00	1.0E-01	4.1E-02
7440-38-2	Arsenic	6.3E-03	5.3E-03	1.3E-03	1.6E-04	6.8E-05
56-55-3	Benz[a]anthracene	5.6E-06	4.1E-06	1.9E-06	4.4E-07	2.2E-07
71-43-2	Benzene	2.8E-02	2.4E-02	5.1E-03	5.1E-04	2.0E-04
207-08-9	Benzo(k)fluoranthene	2.0E-06	1.5E-06	7.0E-07	1.6E-07	7.8E-08
50-32-8	Benzo[a]pyrene	0.0E+00	0.0E+00	0.0E+00	0.0E+00	0.0E+00
205-99-2	Benzo[b]fluoranthene	2.0E-06	1.5E-06	7.0E-07	1.6E-07	7.8E-08
7440-41-7	Beryllium	7.3E-04	5.5E-04	2.3E-04	4.7E-05	2.3E-05
106-99-0	Butadiene, 1,3-	8.0E-03	6.9E-03	1.5E-03	1.4E-04	5.6E-05
7440-43-9	Cadmium	3.0E-03	2.5E-03	6.4E-04	8.7E-05	3.9E-05
18540-29-9	Chromium (Hexavalent) (particulate)	6.1E-03	5.1E-03	1.2E-03	1.4E-04	6.1E-05
218-01-9	Chrysene (Benzo(a)phenanthrene)	3.3E-06	2.4E-06	1.1E-06	2.5E-07	1.3E-07
7440-50-8	Copper	1.1E-03	8.4E-04	3.9E-04	8.9E-05	4.4E-05
53-70-3	Dibenz[a,h]anthracene	2.3E-06	1.7E-06	7.9E-07	1.8E-07	8.8E-08
100-41-4	Ethyl benzene	8.8E-05	6.4E-05	3.0E-05	6.8E-06	3.4E-06
50-00-0	Formaldehyde	1.9E-01	1.5E-01	4.1E-02	6.0E-03	2.7E-03
193-39-5	Indeno(1,2,3-cd)pyrene	2.9E-06	2.2E-06	1.0E-06	2.3E-07	1.1E-07
7439-92-1	Lead	8.7E-03	7.3E-03	1.9E-03	2.6E-04	1.2E-04
7439-96-5	Manganese	4.0E-01	3.4E-01	7.3E-02	7.0E-03	2.8E-03
7439-97-6	Mercury	1.2E-03	9.4E-04	3.1E-04	1.0E-04	4.8E-05
91-20-3	Naphthalene	1.9E-02	1.6E-02	3.7E-03	4.3E-04	1.8E-04
7440-02-0	Nickel	2.9E-03	2.4E-03	6.2E-04	8.5E-05	3.8E-05

Concs

### **Estimated Air Concentrations Used for the AERA**

Facility Name:

Faribault Energy Park

User Title: FEP Combined Cycle Calculations F Air Concentrations in ug/m<sup>3</sup> Total - all stacks CAS # or **Chemical Name** C (1-hr) C (3-hr) C (24-hr) C (monthly) C (annual) MPCA# 10102-44-0 Nitrogen oxide (NO2) 2.5E+01 2.0E+01 6.4E+00 1.0E+00 4.8E-01 Polycyclic Aromatic 130498-29-2 Hydrocarbons (PAH) 2.5E-03 2.1E-03 4.6E-04 4.4E-05 1.8E-05 Polycyclic Organic Matter (POM) 00-01-7 3.0E-03 2.2E-03 1.0E-03 2.3E-04 1.1E-04 7784-49-2 Selenium 1.3E-02 3.3E-03 4.4E-04 2.0E-04 1.5E-02 108-88-3 Toluene 1.5E-01 1.3E-01 2.8E-02 3.1E-03 1.3E-03 1330-20-7 **Xylenes** 1.7E-03 9.5E-02 8.2E-02 1.7E-02 6.7E-04 7440-66-6 Zinc 5.9E-05 2.9E-05 7.7E-04 5.6E-04 2.6E-04 00-03-3 Zinc Compounds 0.0E+00 0.0E+00 0.0E+00 0.0E+00 0.0E+00

	ě	
	읈	
	Ë	
Į	ш	

AERA	
for the	
s Used	
n Rates	
Emission	
Chemical	
Estimated	

υσ#SW2)		Facility Name: User Title: Tyne of emissions	Vame: e: omissions	!		Faribault Energy Park	y Park	ations Februar	<i>σ</i>	Summaries	LA.
TO # SV		User 11th	e: omiceione	ļ				ations rebruar	_		
- 20 # Sγ.)	を見るでは、他们を含めた。 は、これでは、これでは、これでは、これでは、これでは、これでは、これでは、これで	- 1000	21113310111	(e.g., PTE/Future	Actual)	PTE	PTE PTE				
MPCA#	Chemicaliname	HAP	20A	Total Annual Emissions	Stack(s)#	t Turbine	Stack(s)#	Stack(s)#2:Boiler	SUM OF HAPS (TPY)	SUM OF VOCS (TPY)	Criteria Pollutant Sums
				((dh))	Emissions (Bhr)	Annual & Emissions (tps)	Emissions (th/h)	Anguille Entistons (py)	13.886987	7.04175	
202	SO2	ON	ON	118.050000	92.4	115.5	2.05	2.55			118.05
PM10	PM10	Q.	ON	839.149000	984.44	834.99	0.95	4.159	-		839.149
PM2.5	PM2.5	Q	ON								0
NOx	NOx	ON	ON	150.333000	51.85	140.25	2.3	10.083			150.333
	00	Q.	ON	429.502000	1191.48	423.2	1.44	6.302			429.502
Ър	Pb	ON.	ON	0.111580	0.02521	0.11	0.00036	0.00158			0.11158
vocs	VOCs	Q.	NO.	350.052000	1220.74	349.8	0.058	0.252		350.052	
Total HAPs	Total HAPs	ON	Q.	13.884300	3.16	13.82	0.0147	0.0643	13.8843		
0-20-92	Acetaldehyde	YES	YES	0.195700	0.04467	0.1957	0	0	0.1957	0.1957	
107-02-8	Acrolein	YES	YES	0.061300	0.014	0.0613	0	0	0.0613	0.0613	
7664-41-7	Ammonia	ON	ON	92.000000	37.3	92	0	0			
7440-38-2	Arsenic	YES	ON	0.087500	0.01981	0.0868	0.00016	0.0007	0.0875		
56-55-3	Benz[a]anthracene	YES	Q	0.000005	0	0.	0.00000118	0.00000517	5.17E-06		
71-43-2	Benzene	YES	YES	0.434270	ó.09906	0.434	0.0000616	0.00027	0.43427	0.43427	
207-08-9	Benzo(k)fluoranthene	YES	ON	0.000002	0	0	0.000000426	0.00000187	1.87E-06		
50-32-8	Benzo[a]pyrene	YES	ON		0	0	0	0	0		
202-99-2	Benzo[b]fluoranthene	YES	ON	0.000002	0	0	0.000000426	0.00000187	1.87E-06		
7440-41-7	Beryllium	YES	Q	0.002975	0.00056	0.00245	0.00012	0.000525	0.002975		
106-99-0	Butadiene, 1,3-	YES	YES	0.126000	0.02882	0.126	0	0	0.126	0.126	
7440-43-9	Cadmium	YES	ON.	0.038425	0.00864	0.0379	0.00012	0.000525	0.038425		
18540-29-9	Chromium (Hexavalent) (particulate)	YES	ON	0.087325	0.01981	0.0868	0.00012	0.000525	0.087325		
218-01-9	Chrysene (Benzo(a)phenanthrene)	YES	Q Q	0.000003	0	0	0.000000685	0.000003	0.000003		٠
7440-50-8	Copper	O <sub>N</sub>	õ	0.001050	0	0	0.00024	0.00105	·		
53-70-3	Dibenz[a,h]anthracene	YES	YES	0.000002	0	0	0.000000481	0.00000247	2.11E-06	2.11E-06	
100-41-4	Ethyl benzene	YES	YES	0.000080	O	0	0.0000183	0.0000802	0.0000802	0.0000802	
20-00-0	Formaldehyde	YES	YES	2.251600	0.50428	2.21	0.0095	0.0416	2.2516	2.2516	
193-39-5	Indeno(1,2,3-cd)pyrene	YES	YES	0.000003	0	0	0.000000616	0.0000027	0.0000027 0.0000027	0.0000027	

v,
×
7
Š
룓
Ş
Q
ğ
ĕ
ğ
Ķ
Ď
Ϋ́
ş
ĸ
ă
3
Ŗ
÷
- ₫
\$
늄
σ
5
8
ă
퉏
2
Ϋ́
\$
₹
윤
Ω
빌
Ť
ĕ
-2

Estimated Chen	ical E	miss	Emissions Chemical Emission Rates Used for the AERA	Used	Emissions For the A	AERA				
	Facility Name:	Vame:			Faribault Energy Park	Faribault Energy Park			Summaries	ν <sub>0</sub>
	Type of	emissions	Type of emissions (e.g., PTE/Future Actual)	Actual)	PTE	DO TO TO TO	1 2 1 2 1 2 1 2 1 2 1 2 1 2 1 2 1 2 1 2			
	(a)(5)))	(O)	Total Amual Emissions	#(O)(TO PES	il Thurbhne	(S)) pro (S)	Patricia.	SUM OF HAPS (TPY)	SUM OF VOCS (TPY)	Criteria Pollutant Sums
			(((2))		(31) Silotsimei			13:886987	7,0417.5	
	YES	ON	0.111580	0.02521	0.11	0.00036	0,00158	0.11158		
-	YES	NO	6.231050	1.423	6.23	0.00024	0.00105	6.23105		
	YES	ON	0.010515	0.00216	0.009465	0.00012	0.00105	0.010515		
	YES	YES	0.277420	0.06304	0.276	0.000325	0.00142	0.27742	0.27742	
	YES	9	0.036825	0.00828	0.0363	0.00012	0.000525	0.036825		
	9	92	150.333000		0.7			2000		
Polycyclic Aromatic Hydrocarbons (PAH)	YES	S O	0.039400	0.009	0.0394	0	0	0.0394		
	YES	YES	0.002720	0	0	0.00062	0.00272	0.00272	0.00272	
	YES	Q	0.199630	0.04503	261.0	0.0006	0.00263	0.19963		
	YES	YES	2.193420	0.49899	2.1856	0.00178	0.00782	2.19342	2.19342	
	YES	YES	1.499235	0.34227	1.4991	0.00003	0.000135	1.499235	1.499235	
	NO	Q.	0.000701			0.00016				
	Q.	ON								

# H:\Public\Fairbault\EISfiles\RASS-Simple and Combined cycle\EISRASS\_U-20040302 Combined:允S

## Air Dispersion Factors for Estimated Air Concentrations for the AERA

StkDisp

FEP Combined Cycle Calculations February 2004 Ver Faribault Energy Park PTE Facility Name:

(Process (Or other)	Stack(S)#(	#15	Stack(s)#2
1-hr dispersion value from batch process or other air dispersion modeling		2.205	
3-hr dispersion value from batch process or other air dispersion modeling		1.893	27.84
8-hr dispersion value from batch process or other air dispersion modeling		0.9916	20.11
24-hr dispersion value from batch process or other air dispersion modeling		0.4041	13.03
Monthly dispersion value from batch process or other air dispersion modeling		0.03877	2.946
Annual dispersion value from batch process or other air dispersion modeling		0.01547	1.454

Facility Name:	Faribault Energy Park		
User Title:	FEP Combined Cycle Calculations February 2004 Ver	sion	
Chemicals P	otentially Emitted, but Emission Rates wer	e U	navailable
No emissions rates for:	1,4-dichlorobenzene		
	Carbon tetrachloride		
	Tetrachloroethylene		
	Chlorobenzene		
	Chloroform		
	Vinylidene chloride		
	Vinyl chloride		
	Ethylene dichloride	4.7	
	Methylene chloride		
		ME.	

These chemicals plus those for which emission estimates were available are the Chemicals of Potential Interest (COPI)

S
a)
2
æ
>
×

Chemical Name  Chemical Name  Annuoria  Arsenic  Benzolel Jaminacere  Benzolel Jinorantene  Copper  Formadenyde  Indervol (1,2,3-d/)pyene  Formadenyde  Indervol (1,2,3-d/)pyene  Formadene (1,2,3-d/)pyene  Form	Towards Is for the AFRA	Adute Cander Assessment	1	3200 respiratory system HEAST 100	PA 0.03 System; nervous system 7440-38-2 compounds	YES         NO         CALEPA         1.1E-04         9.1E-02         IRIS         30jecreased lymphocyte count	YES NO CALEPA 1.1E-04 9.1E-02	YES NO CALEPA 1.1E-03 9.1E-03	-	YES NO	YES NO HRV 1.8E-03 5.6E-03 CAL EPA 0.03	YES         NO         HRV         1.2E-02         8.3E-04         IRIS         0.1 lower respiratory system	YES NO	NO NO EPA 100 respiratory system compounds	e         YES         YES         HRV         10000 developmental         CALEPA         1.2E-03         8.3E-03         IRIS         10000 developmental toxicity	pue a/a- turaturi	YES YES	YES NO   CAL EPA   1.2E-95   8.3E-91   7439-92-1 compounds	NO CAL reproductive/develo	NO EPA 1.8 pmental	Thoy 9 Nasal Effects, respiratory impacts	Nickel and inflant - respiratory includity operations of the compounds including the compounds operation of the compounds operation of the compounds operation of the compounds of the compound of the compounds of the compound o	NO NO EPA 470 respiratory system	YES NO CAL EPA 1.15-03 9.15-03 50-32-8	PES         YES         YES         YES         CAL EPA         1.1E-03         9.1E-03         50-32-8         Renzolelloyre		HRV 400	YES         HRV         43000 CNS         (NO         NO         NO	NO NO NO	1. An inhalation unit risk of 250 (upim3-14 was calculated using the MDH and USEPA-recommended orial spope factor of 1.4 E-66 (mg TCDD TEOlygidy <sup>1</sup> assuming an inhalation rate of 13.0 m3(day by a 70 kg adult and assuming 100% absorption.  2. Dioun and furan congener concentrations were calculated using the World Health Organizations 1998 Toxic Englement and Particle Conference of Particle Conference Operation May primarily CO-C16 and minimal administrations from Total Petroleum Hydrocarborn Working Group Series. The value can be applied to algebrate petroleum mixtures conference or an inhalation mixtures conference or an inhalation mixtures conference or an inhalation and particle Conference or an inhalation mixtures or an inhala	4. The bronic value may not provide protection for previously-serestized individuals.  The character of the protection of the series of the protection of th	William En An All Controlled and Productive Tollings Annual Controlled Annual Contro	, smaler tran so-uput, assigned by Mr.C.A.	IRIS - Fee Instruction System IRIS - Fee Instruction System CAL EPA - California Office of Environmetal Health Hazard Assessment	Sssment Summary Tables Identify Value
Ammonia  Ammonia  Ammonia  Arsenic  Gradmiun  Berzolki/linora  Berzolki/li			raah? roov	Ŏ.	Q.	YES					YES	YES	YES NO	Q.	YES	4	d)pyrene YES YES	YES	2	<u>g</u>	ZES.	9	NO NO	YES NO	ter YES		YES	YES YES	ON ON spur	260 (ug/m3)-1 was calculated using ner concentrations were calculated us on, Aliphatic value was derived based	not provide protection for previously-s irritancy, but there is little difference b	And the second of the second o	number, smaker man bu-bu-b, assigner of Health Health Risk Value	k Information System	cds Assessment Summary Tables on Control Agency value

### Faribault Energy Park Estimated Mercury Emissions

### Summary of Information Requested in "Assessing the Impacts of Mercury Releases to Ambient Air" (Mercury Guidance)

Prepared by Ned Brooks 3/31/04

### 1. Emissions estimates. (Based on estimates prepared by Marshall Cole 3/29/04, see attached)

Estimated Emissions, lbs/yr

Scenario	Fuel	Emissions factor source	Lbs hg/yr
Simple Cycle	No. 2 distillate		0.78
Min	/Natural Gas		
Combined Cycle	Natural Gas	AP-42 (boilers)	4.19
Combined Cycle	No. 2 Distillate	AP-42 *	18.94*
Combined Cycle	No. 2 Distillate	CATEF	0.31
Combined Cycle	No. 2 Distillate	MPCA sampling of Mn	0.57
	,	No. 2 distillate	

<sup>\*</sup> This is based on EPA's AP-42 emission factor for No. 2 distillate, which has an EPA rating of 'D' (tests were based on a generally unacceptable method but may provide an order of magnitude value for the source).

Using what the MPCA believes to be more reliable emissions factors (California Toxic Emissions Factors database and actual mercury concentration in fuel oil in Minnesota refineries sampled by the MPCA) the MPCA estimates emissions of less than 1 pound per year.

- 2. Current mercury reduction measures. Not required.
- 3. Mercury Flow diagram. (attached)
- 4. Evaluation of Alternatives. Submitted as part of Certificate of Need

### Mercury Emission Factors and Emissions for Natural Gas and No. 2 Distillate Fuel Oil-fired CombustionTurbines

### **SUMMARY**

Fuel	Mercury Emission Factor Source	lb/hr	lb/yr
Natural Gas	AP-42 (boilers; no data for gas	4.78 E-04	4.19
	turbines)		
No. 2 distillate	AP-42	2.16 E-03	18.94
No. 2 distillate	CATEF	3.51 E-05	0.31
No. 2 distillate	Ed Swain data	6.35 E-05	0.56
No. 2 distillate	EPA Locating and Estimating	not calculated - see	discussion
	Documents	below	

### **Natural Gas**

Factor Source: AP-42 ch. 1-4 natural gas combustion in external combustion units/boilers

Factor: 2.6 E-04 lb/10<sup>6</sup> scf of natural gas; EPA factor rating of 'D' which is defined as "Tests that were based on a generally unacceptable method but may provide an order of magnitude value for the source."

Factor is based on tests on 2 boilers with results of 1.76 E-04 lb/mmscf (utility boiler EPRI site 120, April 4, 1993) and 3.34 E-04lb/mmscf (Gibson Oil Refinery industrial boiler, Bakersfield CA May 17, 1990)

To convert to lb/mmBtu,

 $2.6 \text{ E-04 lb/}10^6 \text{ scf * scf/}1020 \text{ Btu} = 2.549 \text{ E-07 lb/mmBtu}$ 

For FEP combined cycle operation, 100% load on natural gas is 1876 mmBtu/hr

1876 mmBtu/hr \* 2.549 E-07 lb/mmBtu = 4.78 E-04 lb/hr \* 8760 hr/yr = 4.19 lb/yr for NG

NOTE: This is the only source I was able to locate for any natural gas Hg emission factor

### No. 2 Distillate Fuel Oil (DFO)

**1DFO.** Factor source: CATEF

1 source tested (industrial cogeneration turbine; date unknown) EPA Factor Rating: E

	lbs/Mgal	lb/mmBtu
Mean:	2.71E-06	1.95 E-08
Median:	1.64E-06	1.18 E-08
Maximum:	5.14E-06	3.70 E-08
Minimum:	1.34E-06	9.64 E-09

For FEP combined cycle operation, use the mean factor value with 100% load on oil at 1801.4 mmBtu/hr

1801.4 mmBtu/hr \* 1.95 E-08 lb/mmBtu = 3.51 E-05 lb/hr \* 8760 hr/yr= 0.3077 lb/yr for No. 2 distillate oil

**2DFO.** Factor Source: AP-42 chapter 3.1, Table 3.1-5

1.2 E-06 lb/mmBtu EPA factor rating 'D'

1801.4 mmBtu/hr \* 1.2 E-06 lb/mmBtu = 2.16 E-03 lb/hr \* 8760 hr/yr = 18.94 lb/yr for No. 2 distillate oil

Factor background data from AP-42 Section 3.1 - Stationary Gas Turbines for Electricity Generation

Facility: Imperial Irrigation, Imperial CA

Date: January 1991

Turbine data: General Electric model NS5000P 46.3 MW power generation, 100% load,

no emission controls; 3 test runs, 2 of which were non-detect

**3DFO.** Factor Source: *Locating and Estimating documents* in EPA CHIEF website, for mercury at this link <a href="http://www.epa.gov/ttn/chief/le/mercury2.pdf">http://www.epa.gov/ttn/chief/le/mercury2.pdf</a> second paragraph page 6-17.

Because only a single mean value was found in the literature for mercury concentration in distillate oil, no conclusions can be drawn about the range of mercury in distillate oil. Table 6-11 lists typical values for mercury in oils, which were obtained by taking the average of the mean values found in the literature. The value for distillate oil is the single data point found in the literature and may not be as representative as the values for residual and crude oils (<0.12 ppmwt).

No emissions data will be calculated using this value.

**4DFO**. Emission based on actual mercury in distillate fuel oil data provided by Ed Swain

Flint Hills and Ashland refineries in Minnesota - samples contain a maximum content of 0.6 ng/milliliter with an average density of 0.87 g/ml (specific gravity of 0.87) which equals a density of 7.25 lb/gal

0.6 ng/ml \* ml/0.87 g = 6.0 E-10 g/8.7 E-01 g = 0.69 ppb by wt (6.9 E-10)

6.9 E-10 \* 7.1 lb/gal \* 12,960 gal/hr = 6.35 E-05 lb/hr \* 8760 hr/yr = 0.56 lb/yr

Note: 12,960 gal/hr is fuel oil consumption rate at maximum heat input of 1801.4 mmBtu/hr and 7.1 lb/gal is assumed density of No. 2 distillate fuel oil